



# BUCS'N BIKES

### "BUGS"

- ★ New, heavy-duty torque converter gives plenty of power for the hill climbs and straightaways
  - ★ Easy to handle with automotive type differential and dual rear wheel brakes
    - ★ New aircraft design tubular frame with tow hitch
- ★ New low profile molded fiberglass body with deep, padded bucket seat
  - ★ Easy to transport in station wagon



Double spring front shocks help cushion the bumps, whether with wheel or optional ski,

	Model No. 711-2 5 H.P.	Model No. 721-2 8 H.P.	Model No. 726-2 8 H.P.			
Frame Construction	Tubular Steel — Argon Welded					
Body Color	Blue Flake					
Tecumseh Engine (All four cycle, air cooled) Displacement (Cu. In.) (C.C.)	5 H.P. %" Shaft 12 198	8 H.P. 1" Shaft 10 30	8 H.P. Electric Star 1" Shaft 3.6			
Engine Shut-Off	Handle Button					
Gas Tank	One Gallon					
Primary Drive	Torque Converter to jack shaft					
Final Drive	No. 420 Chain (H.D. #41)					
Sprocket Ratio	8 Drive 45 Driven					
Differential	Automotive-Type Bevel Gears					
Throttle	Foot Pedal					
Brake — Handle levers	Dual Rear Discs — 8¼" dia.					
Clutch	Torque Converter					
Clutch Ratio	1:1 high 3.9:1 low					
Tires: Front Rear	15" (4.00-6) 18" (9.50-8)	16" (6.50-8) 21" (12-8) A.T.V.				
Body	Fiberglass					
Wheels — with precision ground sealed ball bearings	Steel — Silver gray					
Handlebar and Fender	Chrome Plated					
Frame	Semi-gloss Black					
Seat Cushion	2" Bonded w/1" Bonded Back					
Dimensions: Wheel Base Overall length Overall width Height — Handle Bar Body	70" 51¼" 71" 48" 48" 30½" 31" 25½" 26"					
Frame Ground Clearance	6" 6½"					
Curb Weight	188 lbs.	200 lbs.	212 lbs.			

## "BIKES"

All these trail bikes are equipped with engine exhaust spark arresting mufflers, qualified under U.S. Department of Agriculture Forest Service Standard 5100-1a, Their use is permissible in National Parks.

These bikes are not manufactured for use on public roads, streets or highways.

- ★ Your choice Five Models!
  - ★ "653-2" & "753-2" Complete with headlights, taillights and alternator
- \* All models complete with torque converter









Motocress Handlebar (703-2 and 753-2) Extra strength and durability with chrome motocross handlebar. Adjustable and removable.

Front wheel suspension for "600" and "700" series is integral leading link and shock design.

Stable riding comfort assured with "swing arm" rear suspension on "500" and "700" series. Note 3-point kickstand which is standard on all models.

Model No.	523-2	603-2	653-2	703-2	753-2		
Framě:			bular Twin				
Rake/Bearing	23° Ball	30° Ball		32° B	32° Ball		
Finish Color:	Bittersweet	Bittersweet	& Beige	Bittersweet	-		
Engine (All four-cycle)	4 H.P. 10.5 cu. in./ 172.06 cc Shut-off Button	4 H.P. 4 H.P. W/Alternator 10.5 cu. in./172.06 cc Deluxe Shut-off Button 5 H.P. 5 H.P. W/Alternat 12 cu. in./198 cc Integral Shut-off Button on Handle Bar			N/Alternator 1./198 cc Shut-off on on		
Primary Drive:	Torque Converter to jack shaft**	Asymmetric Torque Converter** to jack shaft					
Speeds	1	Aultiple —	Hand Twis	t Throttle			
Gear Ratio:	12.8:1 Low 4:1 High	19.1:1 Low 6:1 High					
Gas Tank:		3 qt.					
Suspension:	Double External Spring — Front	Leading Link & Shocks — Front					
	Double Spring & Shock — Rear	Swing Arm & Shocks — Rear					
Handle Bars:	Removable Chrome	Adju	vable & stable nrome	Motocross: Removable & Adjustable —Chrome			
Tires:	15" (4.00-6)		6" 0-10)	Front: 18½" (3.00-12) Rear: 17" (3.50-10)			
Wheels:	Steel/Ball Brg. Extended hub	Chrome Wheels/Ball Bearing/ 28 Chrome Spokes					
Brake:	Rear Band	Internal front & rear					
Saddle: (All firm, bonded foam)	18" Deluxe w/Chrome Support	17" Deluxe w/Chrome Support					
Lights:	Model 653-2—Headlight & Taillight, Model 753-2 Hi & Lo Beam Headlight & Taillight						
Foot Rests:	All models have fold back design foot rests.						
Kickstand:	Motorcycle Type — 3-Point						
Dimensions; Wheel Base; Overall Width: Overall Height: Overall Length; Ground Clearance;	40" 24" 35" 53" 5"	39" 26" 36" 55" 6"		41" 28" 37" 58" 6½"			
Weights: Curb Wt. (lbs.) Approx. Ship. Wt. (lbs.)	111 123	115 127	118 129	126 137	128 139		





Specifications subject to change without notice or obligation.





Real going bikes — Columbia! Start up these upstarts and you'll see for yourself. Here is an exciting combination of power, performance and versatility. Trail huggers all the way. Columbia is really what bikes are all about!

Model No. 523-2 [4 H.P.] Complete with Torque Converter

A four horse hotshot that is a do everything trail bike with a lot to offer in performance and economy. Simplicity in design gives the "521" a real feel for the trail. Double spring shocks, front and back, let it take on the cobbiest paths with ease. Grab one and go — confidently.

#### Model Nos. 603-2 [4 H.P.] 653-2 [4 H.P.] Alternator & Lights Complete with Torque Converter

A real trail blazin' buddy! Rugged. Ready. Reliable. Handles rough terrain with unquestioned authority. Exclusive leading link suspension cushions shocks more evenly while assymetric torque converter puts power where you need it . . . when you need it. Against others in its class, there's nothing to compare.



#### MINI-CYCLE Model Nos. 703-2 [5 H.P.] 753-2 [5 H.P.] Alternator & Lights

This is the "Big One" in everything, except size and price. Five horses give it quickness to match its strength. It's the most rugged performer in its class with a 32° fork rake design to give maximum stability and exceptional maneuverability — a tough combination to match.



